SAFETY DATA SHEET TOKUYAMA UNIVERSAL BOND BOND A

1. Identification

Product identifier

Product name TOKUYAMA UNIVERSAL BOND BOND A

Recommended use of the chemical and restrictions on use

Application Dental adhesive. For dental professionals only.

Details of the supplier of the safety data sheet

Supplier Tokuyama Dental America, Inc.

740 Garden View CT., Suite 200 Encinitas,

CA 92024 U.S.A.

Tel: (877) 378 3548 (Toll-Free)

Tel: (760)942-7211 Fax: (760)942-7212

Contact Person http://www.tokuyama-dental.com/tdc/contact.html

Manufacturer Tokuyama Dental Corporation

38-9, Taitou 1-chome, Taitou-ku, Tokyo

110-0016, Japan TEL: +81-3-3835-2261 FAX: +81-3-3835-2265

Emergency telephone number

Emergency telephone California Poison Control System - San Francisco Division

San Francisco General Hospital

Bldg 5 Rm 2A21,1001 Potrero Ave, San Francisco Emergency telephone number: +1 800 222 1222

E-mail address: coadmin@calpoison.org

http://www.calpoison.org

National Capital Poison Center

3201 New Mexico Ave, Ste 310, Washington DC Emergency telephone number: +1 800 222 1222

Telephone number: +1 202 362 3867 Facsimile numer: +1 202 362 8377 E-mail address: pc@poison.org

http://www.poison.org

2. Hazard(s) identification

Classification of the substance or mixture

OSHA Regulatory Status This Product is Hazardous under the OSHA Hazard Communication Standard.

Physical hazards Flam. Liq. 2 - H225

Health hazards Skin Irrit. 2 - H315: Eye Irrit. 2A - H319: Skin Sens. 1 - H317: STOT SE 3 - H336

Environmental hazards Not Classified

Label elements

TOKUYAMA UNIVERSAL BOND BOND A

Pictogram





Signal word Danger

Hazard statements H225 Highly flammable liquid and vapor.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction. H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

Precautionary statements

P210 Keep away from heat, sparks, open flames and hot surfaces. No smoking.

P240 Ground/ bond container and receiving equipment.

P241 Use explosion-proof electrical equipment.

P242 Use only non-sparking tools.

P243 Take precautionary measures against static discharge.

P261 Avoid breathing vapor/ spray.

P264 Wash contaminated skin thoroughly after handling. P271 Use only outdoors or in a well-ventilated area.

P272 Contaminated work clothing must not be allowed out of the workplace.
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

P302+P352 If on skin: Wash with plenty of water.

P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse

skin with water/ shower.

P304+P340 If inhaled: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing. P312 Call a poison center/ doctor if you feel unwell.

P321 Specific treatment (see medical advice on this label).

P332+P313 If skin irritation occurs: Get medical advice/ attention.

P333+P313 If skin irritation or rash occurs: Get medical advice/ attention.

P337+P313 If eye irritation persists: Get medical advice/ attention. P362+P364 Take off contaminated clothing and wash it before reuse.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P403+P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

P370+P378 In case of fire: Use alcohol resistant foam, carbon dioxide or dry powder to

extinguish.

P501 Dispose of contents/ container in accordance with local regulations.

Contains

ACETONE, 2-PROPENOIC ACID, 2-METHYL-, (1-METHYLETHYLIDENE)BIS[4,1-PHENYLENEOXY(2-HYDROXY-3,1-PROPANEDIYL)] ESTER, 2-HYDROXYETHYL

METHACRYLATE, TRIETHYLENE GLYCOL DIMETHACRYLATE

Other hazards

Hazards not otherwise classified (HNOC)

Not applicable.

3. Composition/information on ingredients

Mixtures

ACETONE 30-60%

CAS number: 67-64-1

TOKUYAMA UNIVERSAL BOND BOND A

2-PROPENOIC ACID, 2-METHYL-, (1-

METHYLETHYLIDENE)BIS[4,1-PHENYLENEOXY(2-

HYDROXY-3,1-PROPANEDIYL)] ESTER

CAS number: 1565-94-2

2-HYDROXYETHYL METHACRYLATE

10-30%

10-30%

CAS number: 868-77-9

TRIETHYLENE GLYCOL DIMETHACRYLATE

5-10%

CAS number: 109-16-0

METHACRTYLOXYALKYL ACID PHOSPHATE

1-5%

(PHOSPHORIC ACID MONOMER)

CAS number: 52628-03-2

2,6-DI-tert-BUTYL-p-CRESOL

<1%

CAS number: 128-37-0 M factor (Chronic) = 1

4. First-aid measures

Description of first aid measures

General information Get medical attention if any discomfort continues. Show this Safety Data Sheet to the medical

personnel.

Inhalation Move affected person to fresh air and keep warm and at rest in a position comfortable for

breathing. When breathing is difficult, properly trained personnel may assist affected person

by administering oxygen. Get medical attention.

Ingestion Rinse mouth thoroughly with water. Give a few small glasses of water or milk to drink. Never

give anything by mouth to an unconscious person. Keep affected person under observation.

Get medical attention.

Skin Contact Wash skin thoroughly with soap and water. In the event of any sensitization symptoms

developing, ensure further exposure is avoided. Get medical attention if symptoms are severe

or persist after washing.

Eye contact Rinse immediately with plenty of water. Remove contact lenses, if present and easy to do.

Continue rinsing. Get medical attention if any discomfort continues.

Protection of first aiders First aid personnel should wear appropriate protective equipment during any rescue.

Most important symptoms and effects, both acute and delayed

General information The severity of the symptoms described will vary dependent on the concentration and the

length of exposure.

Inhalation May cause drowsiness or dizziness.

Skin contact Irritating to skin. May cause an allergic skin reaction. Repeated exposure may cause skin

dryness or cracking.

Eye contact Irritating to eyes.

Indication of immediate medical attention and special treatment needed

TOKUYAMA UNIVERSAL BOND BOND A

Notes for the doctor Treat symptomatically.

5. Fire-fighting measures

Extinguishing media

Suitable extinguishing media Highly flammable gases or vapors. Extinguish with alcohol-resistant foam, carbon dioxide, dry

powder or water fog. Use fire-extinguishing media suitable for the surrounding fire.

Unsuitable extinguishing

media

Do not use water jet as an extinguisher, as this will spread the fire.

Special hazards arising from the substance or mixture

Specific hazards Highly flammable liquid and vapour. Containers can burst violently or explode when heated,

> due to excessive pressure build-up. Vapors may be ignited by a spark, a hot surface or an ember. Vapors may form explosive mixtures with air. Fire-water run-off in sewers may create

fire or explosion hazard.

Hazardous combustion

products

Thermal decomposition or combustion products may include the following substances: Harmful gases or vapors. Irritating gases or vapors. Carbon monoxide (CO). Carbon dioxide

Advice for firefighters

Protective actions during firefighting

Avoid breathing fire gases or vapors. Evacuate area. Keep upwind to avoid inhalation of gases, vapors, fumes and smoke. Ventilate closed spaces before entering them. Cool containers exposed to heat with water spray and remove them from the fire area if it can be done without risk. Cool containers exposed to flames with water until well after the fire is out. If a leak or spill has not ignited, use water spray to disperse vapors and protect men stopping the leak. Control run-off water by containing and keeping it out of sewers and watercourses.

Special protective equipment for firefighters

Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing. Standard Firefighter's clothing including helmets, protective boots and gloves will provide a basic level of protection for chemical incidents.

6. Accidental release measures

Personal precautions

Personal precautions, protective equipment and emergency procedures

(CO2).

Wear protective clothing as described in Section 8 of this safety data sheet. No action shall be taken without appropriate training or involving any personal risk. Evacuate area. Provide adequate ventilation. No smoking, sparks, flames or other sources of ignition near spillage. Promptly remove any clothing that becomes contaminated. Avoid inhalation of dust and vapors. Use suitable respiratory protection if ventilation is inadequate. Avoid contact with skin

and eyes.

Environmental precautions

Environmental precautions Avoid discharge into drains or watercourses or onto the ground.

Methods and material for containment and cleaning up

Methods for cleaning up

Wear protective clothing as described in Section 8 of this safety data sheet. No smoking, sparks, flames or other sources of ignition near spillage. Eliminate all ignition sources if safe to do so. Use only non-sparking tools. Contain and absorb spillage with sand, earth or other non-combustible material. Collect and place in suitable waste disposal containers and seal securely. Do not allow material to enter confined spaces, due to the risk of explosion. Wash thoroughly after dealing with a spillage. For waste disposal, see Section 13.

Reference to other sections

For personal protection, see Section 8. See Section 11 for additional information on health hazards. See Section 12 for additional information on ecological hazards. For waste disposal, see Section 13.

TOKUYAMA UNIVERSAL BOND BOND A

7. Handling and storage

Precautions for safe handling

Usage precautions

Wear protective clothing as described in Section 8 of this safety data sheet. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use explosion-proof electrical, ventilating and lighting equipment. Use only non-sparking tools. Ground/bond container and receiving equipment. Take precautionary measures against static discharges. Avoid breathing gas, fume, vapours or spray. Handle all packages and containers carefully to minimize spills. Avoid the formation of mists. Keep container tightly sealed when not in use. Do not handle broken packages without protective equipment. Keep away from food, drink and animal feeding stuffs.

Advice on general occupational hygiene

Do not eat, drink or smoke when using this product. Wash at the end of each work shift and before eating, smoking and using the toilet. Wash promptly if skin becomes contaminated. Take off contaminated clothing and wash before reuse. Wash contaminated clothing before reuse.

Conditions for safe storage, including any incompatibilities

Storage precautions

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep container tightly closed, in a cool, well ventilated place. Store locked up. Keep only in the original container. Protect containers from damage. Store away from the following materials: Oxidizing materials. Organic peroxides/hydroperoxides.

Specific end uses(s)

Specific end use(s)

The identified uses for this product are detailed in Section 1.2.

8. Exposure Controls/personal protection

Control parameters

Occupational exposure limits

ACETONE

Long-term exposure limit (8-hour TWA): ACGIH 250 ppm 594 mg/m³ Short-term exposure limit (15-minute): ACGIH 500 ppm 1187 mg/m³

A4

Long-term exposure limit (8-hour TWA): OSHA 1000 ppm 2400 mg/m³

2,6-DI-tert-BUTYL-p-CRESOL

Long-term exposure limit (8-hour TWA): ACGIH 2 mg/m³ inhalable fraction and vapor

Α4

ACGIH = American Conference of Governmental Industrial Hygienists.

A4 = Not Classifiable as a Human Carcinogen.

OSHA = Occupational Safety and Health Administration.

Exposure controls

Appropriate engineering

controls

Provide adequate ventilation. Use explosion-proof electrical, ventilating and lighting equipment. Observe any occupational exposure limits for the product or ingredients.

Eye/face protection Wear tight-fitting, chemical splash goggles or face shield.

Hand protection

Wear protective gloves. The most suitable glove should be chosen in consultation with the glove supplier/manufacturer, who can provide information about the breakthrough time of the glove material. To protect hands from chemicals, gloves should comply with OSHA 1910.138 and be demonstrated to be impervious to the chemical and resist degradation. Considering the data specified by the glove manufacturer, check during use that the gloves are retaining their protective properties and change them as soon as any deterioration is detected.

Frequent changes are recommended.

TOKUYAMA UNIVERSAL BOND BOND A

Other skin and body

protection

Odor

Wear appropriate clothing to prevent repeated or prolonged skin contact.

Hygiene measures Wash hands thoroughly after handling. Wash at the end of each work shift and before eating,

smoking and using the toilet. Do not eat, drink or smoke when using this product. Take off

immediately all contaminated clothing and wash it before reuse.

Respiratory protection Ensure all respiratory protective equipment is suitable for its intended use and is NIOSH

approved. Check that the respirator fits tightly and the filter is changed regularly. Gas and combination filter cartridges should comply with OSHA 1910.134. Full face mask respirators with replaceable filter cartridges should comply with OSHA 1910.134. Half mask and quarter mask respirators with replaceable filter cartridges should comply with OSHA 1910.134.

9. Physical and Chemical Properties

Information on basic physical and chemical properties

Appearance Liquid

Color Colorless ~ Yellow

Odor threshold

PH

Not available.

Melting point

Not available.

Initial boiling point and range >35°C

Flash point -17.6°C

Evaporation rate Not available.

Flammability (solid, gas) Not available.

Upper/lower flammability or

explosive limits

Not available.

Characteristic

Vapor pressure Not available.

Vapor density Not available.

Relative density 0.968

Solubility(ies) No information available.

Partition coefficientNot available.Auto-ignition temperatureNot available.Decomposition TemperatureNot available.ViscosityNot available.Explosive propertiesNot available.Oxidizing propertiesNot available.

10. Stability and reactivity

Reactivity The following materials may react violently with the product: Oxidizing materials. Organic

peroxides/hydroperoxides. See the other subsections of this section for further details.

TOKUYAMA UNIVERSAL BOND BOND A

Stability Stable at normal ambient temperatures and when used as recommended. Stable under the

prescribed storage conditions.

Possibility of hazardous

reactions

The following materials may react strongly with the product: Oxidizing materials. Organic

peroxides/hydroperoxides.

Conditions to avoid Vapors may form explosive mixtures with air. Containers can burst violently or explode when

heated, due to excessive pressure build-up. Static electricity and formation of sparks must be

prevented.

Materials to avoid Oxidizing materials. Organic peroxides/hydroperoxides.

Hazardous decomposition

products

Thermal decomposition or combustion products may include the following substances: Harmful gases or vapors. Irritating gases or vapors. Carbon monoxide (CO). Carbon dioxide

(CO2).

11. Toxicological information

Information on toxicological effects

Routes of exposure Skin , Eyes , Ingestion , Inhalation , Health effects: See section 4.

Acute toxicity - oral

Notes (oral LD₅₀) Not available.

Acute toxicity - dermal

Notes (dermal LD₅₀) Not available.

Acute toxicity - inhalation

Notes (inhalation LC50) Not available.

Skin corrosion/irritation

Skin corrosion/irritation Skin Irrit. 2 - H315, Irritating to skin.

Animal data Not available.

Serious eye damage/irritation

Serious eye damage/irritation Eye Irrit. 2 - H319 Causes serious eye irritation.

Respiratory sensitization

Respiratory sensitization Not available.

Skin sensitization

Skin sensitization Skin Sens. 1 - H317 May cause an allergic skin reaction.

Germ cell mutagenicity

Genotoxicity - in vitro Not available.

Carcinogenicity

Carcinogenicity Not available.

IARC carcinogenicity

Some of the ingredients are listed or exempt. IARC Group 3 Not classifiable as to its

carcinogenicity to humans.

NTP carcinogenicity Some of the ingredients are listed or exempt.

OSHA Carcinogenicity None of the ingredients are listed.

Reproductive toxicity

Reproductive toxicity - fertility Not available.

TOKUYAMA UNIVERSAL BOND BOND A

Reproductive toxicity -

development

Not available.

Specific target organ toxicity - single exposure

STOT - single exposure STOT SE 3 - H336 May cause drowsiness or dizziness.

Target organs Central nervous system

Specific target organ toxicity - repeated exposure

STOT - repeated exposure Not classified as a specific target organ toxicant after repeated exposure.

Aspiration hazard

Aspiration hazard Not available.

Toxicological information on ingredients.

SILICON DIOXIDE

Carcinogenicity

IARC Group 3 Not classifiable as to its carcinogenicity to humans.

NTP carcinogenicity Reasonably anticipated to be a human carcinogen.

OSHA Carcinogenicity Not listed.

2,6-DI-tert-BUTYL-p-CRESOL

Carcinogenicity

IARC Group 3 Not classifiable as to its carcinogenicity to humans.

NTP carcinogenicity Reasonably anticipated to be a human carcinogen.

OSHA Carcinogenicity Not listed.

12. Ecological Information

Toxicity

Toxicity No information available.

Acute toxicity - fish Not available.

Acute toxicity - aquatic

Not available.

invertebrates

Acute toxicity - aquatic plants Not available.

Persistence and degradability

Persistence and degradability The degradability of the product is not known.

Bioaccumulative potential

Bio-Accumulative Potential No data available on bioaccumulation.

Partition coefficient Not available.

Mobility in soil

Mobility Volatile liquid. The product contains organic solvents which will evaporate easily from all

surfaces.

Results of PBT and vPvB assessment

TOKUYAMA UNIVERSAL BOND BOND A

Results of PBT and vPvB

assessment

This product does not contain any substances classified as PBT or vPvB.

Other adverse effects

Other adverse effects None known.

13. Disposal considerations

Waste treatment methods

General information

The generation of waste should be minimized or avoided wherever possible. Reuse or recycle products wherever possible. This material and its container must be disposed of in a safe way. When handling waste, the safety precautions applying to handling of the product should be considered. Care should be taken when handling emptied containers that have not been thoroughly cleaned or rinsed out. Empty containers or liners may retain some product residues and hence be potentially hazardous.

Disposal methods

Dispose of surplus products and those that cannot be recycled via a licensed waste disposal contractor. Waste, residues, empty containers, discarded work clothes and contaminated cleaning materials should be collected in designated containers, labeled with their contents. Incineration or landfill should only be considered when recycling is not feasible.

14. Transport information

General For limited quantity packaging/limited load information, consult the relevant modal

documentation using the data shown in this section.

UN Number

UN No. (IMDG) 1133 UN No. (ICAO) 1133 UN No. (DOT) UN1133

UN proper shipping name

Proper shipping name (IMDG) ADHESIVES
Proper shipping name (ICAO) ADHESIVES
Proper shipping name (DOT) ADHESIVES

Transport hazard class(es)

DOT hazard class 3
DOT hazard label 3
IMDG Class 3
ICAO class/division 3

Transport labels



DOT transport labels



TOKUYAMA UNIVERSAL BOND BOND A

Packing group

IMDG packing group ||

ICAO packing group ||

DOT packing group

Environmental hazards

Environmentally Hazardous Substance

No.

Special precautions for user

Always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

EmS F-E, S-D

Transport in bulk according to Not applicable.

Annex II of MARPOL 73/78

and the IBC Code

15. Regulatory information

Regulatory Status This Product is Hazardous under the OSHA Hazard Communication Standard.

International Regulations

US Federal Regulations

SARA Section 302 Extremely Hazardous Substances Tier II Threshold Planning Quantities

None of the ingredients are listed or exempt.

CERCLA/Superfund, Hazardous Substances/Reportable Quantities (EPA)

The following ingredients are listed or exempt:

ACETONE

Final CERCLA RQ: 5000(2270) pounds (Kilograms)

SARA Extremely Hazardous Substances EPCRA Reportable Quantities

None of the ingredients are listed or exempt.

SARA 313 Emission Reporting

None of the ingredients are listed or exempt.

CAA Accidental Release Prevention

None of the ingredients are listed or exempt.

FDA - Essential Chemical

None of the ingredients are listed or exempt.

FDA - Precursor Chemical

None of the ingredients are listed or exempt.

SARA (311/312) Hazard Categories

Fire Acute Chronic

OSHA Highly Hazardous Chemicals

None of the ingredients are listed or exempt.

TOKUYAMA UNIVERSAL BOND BOND A

US State Regulations

California Proposition 65 Carcinogens and Reproductive Toxins

None of the ingredients are listed or exempt.

California Air Toxics "Hot Spots" (A-I)

The following ingredients are listed or exempt:

SILICON DIOXIDE

Present.

California Air Toxics "Hot Spots" (A-II)

None of the ingredients are listed or exempt.

California Directors List of Hazardous Substances

The following ingredients are listed or exempt:

2,6-DI-tert-BUTYL-p-CRESOL

Present.

SILICON DIOXIDE

Present.

ACETONE

Present.

Massachusetts "Right To Know" List

The following ingredients are listed or exempt:

2,6-DI-tert-BUTYL-p-CRESOL

Present.

SILICON DIOXIDE

Present.

ACETONE

Present.

Rhode Island "Right To Know" List

The following ingredients are listed or exempt:

2,6-DI-tert-BUTYL-p-CRESOL

Present.

ACETONE

Present.

Minnesota "Right To Know" List

The following ingredients are listed or exempt:

2,6-DI-tert-BUTYL-p-CRESOL

Present.

SILICON DIOXIDE

Present.

ACETONE

Present.

New Jersey "Right To Know" List

The following ingredients are listed or exempt:

TOKUYAMA UNIVERSAL BOND BOND A

2,6-DI-tert-BUTYL-p-CRESOL

Present.

ACETONE

Present.

Pennsylvania "Right To Know" List

The following ingredients are listed or exempt:

2,6-DI-tert-BUTYL-p-CRESOL

Present.

SILICON DIOXIDE

Present.

ACETONE

Present.

16. Other information

Revision comments This is first issue.

Revision date 11/20/2016

Revision

Hazard statements in full H225 Highly flammable liquid and vapor.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction. H319 Causes serious eye irritation. H336 May cause drowsiness or dizziness.

The information which is contained in this document is based on available data. However, as such has been obtained from various sources, including independent laboratories, it is given without warranty or representation that is complete, accurate and can be replied upon. Tokuyama Dental Corp. has not attempted to conceal in any way the deleterious aspects of the product listed herein, but makes no warranty as to such information.